

WIRE BRUSHES

LK wire brushes are available in several different styles for use by hand or with power tools such as angle grinders, bench grinders and drills. Brush fills include steel, stainless steel and brass to provide assorted options for removing rust, corrosion, paint, welding splatter and general surface de-burring on many materials.

Applications are wide ranging and include cleaning metal surfaces prior to welding or painting, while softer brushes may be used on porous surfaces such as timber and board materials.

SHAFT MOUNTED BRUSHES

These brushes are supplied complete with 6.5mm (1/4in) shanks and they are designed for use on power tools with a maximum speed of 4,500rpm. Crimped wire brushes are designed for light to medium-duty and general purpose applications and they are available in circular, cup and end faced alternatives.

SHAFT MOUNTED CIRCULAR BRUSHES - Crimped Steel Wire

CODE	TYPE	DIAMETER	SHAFT	WIRE	ART. NO.
WB-SCR-50-C-CS	SHAFT/CIR	50 mm	6 mm	CS	10.1.1.3.18
WB-SCR-75-C-CS	SHAFT/CIR	75 mm	6 mm	CS	10.1.1.3.19
WB-SCR-100-C-CS	SHAFT/CIR	100 mm	6 mm	CS	10.1.1.3.20

SHAFT MOUNTED CUP BRUSHES - Crimped Steel Wire

CODE	TYPE	DIAMETER	SHAFT	WIRE	ART. NO.
WB-SCUP-50-C-CS	SHAFT/CUP	50 mm	6 mm	CS	10.1.1.3.21
WB-SCUP-75-C-CS	SHAFT/CUP	75 mm	6 mm	CS	10.1.1.3.22

CIRCULAR BRUSHES - Crimped Steel Wire

Two brush diameters for use on bench mounted grinders, and supplied complete with two plastic adaptors (13 & 25mm) for converting them for use on most commonly used bench grinders.

CODE	TYPE	DIAMETER	BORE	WIRE	ART. NO.
WB-WH-115-C-CS	WHEEL	115 mm	32mm	CS	10.1.1.3.13
WB-WH-150-C-CS	WHEEL	150 mm	32mm	CS	10.1.1.3.14
WB-WH-180-C-CS	WHEEL	180 mm	32mm	CS	10.1.1.3.15
WB-WH-200-C-CS	WHEEL	200mm	32mm	CS	10.1.1.3.15

LIEMKE GmbH&Co. KG

Industriestr. 33
33689 Bielefeld
Germany
Tel. +49 (0) 5205 9987488
Fax +49 (0) 5205 9987487
info@liemke.com

All brushes conform to
ISO9001. and DIN EN1083-1 and 2



CIRCULAR KNOT BRUSHES - Flat Twisted Steel Wire

Flat twist-knot brushes are available in two versions with the 115mm (4½in) model supplied with an M14 thread arbor for direct mounting onto an appropriate angle grinder. The second alternative has a 22.2mm bore for use with standard angle grinder flange plates.

CIRCULAR BRUSHES - Twisted Wire

CODE	TYPE	DIAMETER	BORE	WIRE	ART. NO.
WB-WH-115-T-CS	WHEEL	115 mm	32 mm	CS	10.1.1.3.9
WB-WH-150-T-CS	WHEEL	150 mm	32 mm	CS	10.1.1.3.10
WB-WH-115-T-CS	WHEEL	180 mm	32 mm	CS	10.1.1.3.11
WB-WH-180-T-CS	WHEEL	200 mm	32 mm	CS	10.1.1.3.12

THREADED BRUSHES

These brushes are supplied fitted with a threaded arbor for use on angle grinders from 100mm (4in) up to higher rated and more powerful 230mm (9in) machines. They are available in a crimped or heavy-duty twist-knot versions, and they are designed for industrial work and for specialist applications.

CUP BRUSHES - Crimped Wire

CODE	TYPE	DIAMETER	THREAD	WIRE	ART. NO.
WB-CUP-75-C-CS	CUP	75 mm	M14	CS	10.1.1.3.5
WB-CUP-75-C-CS	CUP	75 mm	M14	CS	10.1.1.3.5
WB-CUP-100-C-CS	CUP	100 mm	M14	CS	10.1.1.3.6
WB-CUP-75-C-CS	CUP	75 mm	M14	CS	10.1.1.3.7
WB-CUP-100-C-CS	CUP	75 mm	M14	CS	10.1.1.3.8

CUP BRUSHES - Twisted Wire

CODE	TYPE	DIAMETER	THREAD	WIRE	ART. NO.
WB-CUP-65-T-CS	CUP	65 mm	M10	CS	10.1.1.3.17
WB-CUP-75-T-CS	CUP	75 mm	M14	CS	10.1.1.3.1
WB-CUP-100-T-CS	CUP	100 mm	M14	CS	10.1.1.3.2
WB-CUP-75-T-CS	CUP	75 mm	M14	SS	10.1.1.3.3
WB-CUP-100-T-CS	CUP	100 mm	M14	SS	10.1.1.3.4

SAFETY TIP

- Never exceed the maximum RPM as indicated on the brush.
- Always follow the manufacturer's instructions when using this product with a power tool.
- Apply light pressure while brushing to allow the tips of the brush to work efficiently. Increased pressure will reduce the effectiveness and life of the brush.